

T2



Compact 43 cm Scrubber-Dryer

- Experience Tennant performance while maintaining your budget
- Clean small, congested spaces easily
- Deliver superior cleaning & floor safety compared with manual mopping methods
- Lower fatigue and increase operator satisfaction with low push force pad-assistance



Dramatically improve cleanliness and safety in small spaces.

Enhance productivity

Increase operation efficiency by completely cleaning and drying small, congested areas in one-pass. Additionally, Tennant T-series durability ensures maximum machine uptime.

Ensure superior cleaning performance

Provide the highest level of cleanliness with 23 kg of down pressure and 230 rpm agitation – all delivered through a 0.75 kW brush motor; the most powerful in its class.

Maintain maximum hygiene

Reduce scrubber tank mold and bacteria with Tennant's easy-to-clean Hygenic® recovery tank and debris tray.



ENGINEERED FOR ENVIRONMENTAL SAFETY

Increase indoor environmental quality

Provide “anytime” operation with whisper-quiet 68 dBA sound level while optional maintenance free batteries lower emissions, improving indoor air-quality.

Maximise operational safety

Brush assist action only occurs when an operator engages the ergonomic “safety triggers” while scrubbing.

Reduce risk of slip-and-fall accidents

Unsurpassed water recovery leaves small, congested spaces ready for foot traffic immediately.



Experience the industry's benchmark T-series, with the affordable T2 scrubber.

Enhance operator comfort and reduce fatigue with ergonomic adjustable, “safety trigger” handle design.



Tennant's unique pad driver and squeegee holder make transporting or storing the T2 simple and easy.



Easily train new operators with the industry's most simplified controls – just power on and activate the triggers.



Optimise machine sanitisation with an easy clean-out rotomold recovery tank and debris tray.



T-SERIES SCRUBBERS

T-Series scrubbers optimise your facility health and safety with industry leading noise-levels and water recovery along with exclusive, fully-cleanable Hygenic® tanks.

T1 380 MM

Cord-electric scrubber-dryer with unmatched bi-directional water recovery and exclusive Insta-Adjust™ handle.



T2 430 MM

Experience cordless freedom with Tennant's smallest, most affordable battery scrubber-dryer.



T3 430, 510 MM

Ultra-quiet operation can now be combined with award winning FaST® or electrically activated water technology and fully-cleanable Hygenic tanks.



T5 610-810 MM

Maximise quality assurance through the T5's exclusive QA Controls™ – locking in key scrub settings or FaST or electrically activated water technologies.



T7 660-810 MM

Maximise comfort, agility and run time with a compact rider that features productivity enhancing Economy Mode.



T2 WALK-BEHIND AUTOMATIC SCRUBBER

FEATURES

Scrubbing System

Cleaning path	430 mm	17 in
Solution tank capacity	26 L	6.9 gal

Productivity (per hour)

Theoretical Max	1,900 m ²	20,230 ft ²
Estimated Coverage*	672 m ²	7,234 ft ²

Drive System

Brush motor horsepower	0.75 kW	1.0 hp
Brush RPM	230 rpm	230 rpm
Brush/pad pressure	23 kg	50 lbs

Recovery System

Recovery tank description	Full access & cleanable	
Recovery tank capacity (includes demisting chamber)	36 L	9.5 gal
Vacuum motor	0.30 kW – two stage	0.4 hp – two stage
Vac motor CFM	1.84 m ³	65 cfm
Vac motor sealed waterlift	1,020 mm	40 in

Battery System

Lead Acid / Run time**	(2) 12V, 105 AH / Up to 2 hours
------------------------	---------------------------------

Dimensions/Weights

Product height	930 mm	36.6 in
Product length	1,120 mm	44.1 in
Product width (with squeegee)	695 mm	27.4 in
Product weight (with batteries)	136 kg	300 lbs

Decibel Rating

Operator's position***	68 dBA
------------------------	--------

Warranty

1 year on parts and labor or 2000 hours.
10 years on rotationally-molded polyethylene tanks.

*Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

** Run times are based on Continuous Scrubbing Run Times.

*** For CE compliance, sound level is measured as an A-weighted sound pressure level per ISO 11201 and reported in accordance with ISO 4871.

SEEING IS BELIEVING

For a demonstration or additional information, send an email to australia@tennantco.com.

©2009 The Tennant Company logo and other marks designated with the symbol "®" are registered trademarks of Tennant Company, Inc., in the United States and/or other countries. The marks designated with "TM" are trademarks of Tennant Company that are not yet registered in the United States.

Tennant Company

Unit 2, Block Y
391 Park Road
(PO Box 116)
Regents Park NSW 2143 Australia

Sales: 1800 226 843
Service: 1800 008 815
Parts: 1800 008 805
Outside Australia: +61 2 8718 9718
Fax: +61 2 8718 9719

Email: australia@tennantco.com
www.tennantco.com.au